

CEE-BEE® F-19



LEAK DETECTOR

CEE-BEE® BUBBLE FLUID F-19 is a detection fluid used for detecting leaks within an aircraft's low and high pressure oxygen systems.

BENEFITS

- Rapid and effective leak detecting method. Leak areas easily located
- Compatible with oxygen
- Safe on most metals, including aluminum, steel and copper alloys
- Safe on good quality paints and most plastics
- Non-flammable • Surfactants biodegradable

PHYSICAL PROPERTIES

Appearance	Liquide	Solubility	Water soluble	Flammability	Non-flammable
Colour	Colourless	pH	7-8	Density	1.00 g/ml
Odor	Odourless	Flash Point	N/A		

AVAILABLE FORMATS



19L

20CBF19P

208L

20CBF19D

1000L

20CBF19T

APPROBATIONS

- LOCKHEED EPS 31.211
- MIL-L-25567D, TYPE I

USE PROCEDURES

1. Apply a thin layer of detection fluid by brush, or from tip of a plastic squeeze bottle, to all fittings, connections, and check valves. Leaks can be readily located by the formation of bubbles where the oxygen is escaping.
2. After inspection is complete, all bubble fluid must be completely removed from the surface. Thoroughly wipe surface clean, with damp cloths, or rinse with water.

LEGISLATION

- WHMIS Regulated

SAFETY & HANDLING

- Refer to Safety Data Sheet (SDS) for additional information
- Dispose of container and its contents in compliance with all applicable regulations.
- Avoid eye and skin contact. May cause irritation. • Do not ingest. • In case of accidental contact, flush affected areas with water. If irritation persists, seek medical attention.

Information and recommendations regarding this product are presented in good faith. However no guarantees are associated with the data presented in this document, and no such guarantees should be interpreted from the information and expected results presented. We do not assume any liability for damage, loss or injury, direct or indirect, related to the use of this product.

Revised: 07 2020